



DUCHESNE COUNTY MONUMENT SURVEY RECORD

T1S R1W
1/4

SEC 19 | SEC 20

U.S.B.&M.


L-5



SCALE: 1"=30'



5/8"X24" REBAR WITH A 2 1/2"
ALUMINUM DUCHESNE COUNTY
MONUMENT AT SECTION CORNER



NOTE:
THE BASIS OF BEARINGS IS GEODETIC NORTH DERIVED
FROM G.P.S. OBSERVATIONS AT A CONTROL POINT
(SECTION CORNER) LOCATED AT LAT. 40°23'20.57790"N
AND LONG. 110°01'46.98583"W USING THE UTAH STATE
G.P.S. VIRTUAL REFERENCE STATION CONTROL NETWORK
MAINTAINED AND OPERATED BY THE AUTOMATED
GEOGRAPHIC REFERENCE CENTER

5/8"X24" REBAR WITH A 2 1/2"
ALUMINUM DUCHESNE COUNTY
MONUMENT AT SECTION CORNER

DESCRIPTION OF CORNER EVIDENCE FOUND

FOUND MONUMENT SPIKE (HARROW
TOOTH) AT POSITION OF THE 1/4
CORNER



DESCRIPTION OF MONUMENT AND ACCESSORIES
ESTABLISHED TO PERPETUATE THE ORIGINAL
LOCATION OF THE CORNER

SET A 5/8"X24" REBAR WITH A 2 1/2"
ALUMINUM DUCHESNE COUNTY
MONUMENT AT THE POSITION OF THE 1/4
CORNER AFTER ROAD CONSTRUCTION

STATE PLANE COORDINATE DATA

(U.S. SURVEY FEET)
NAD83 UTAH CENTRAL ZONE
N: 7311167.531
E: 2049996.303
NAVD88 EL: 5648.64'

LATITUDE: 40°22'54.47501" N
LONGITUDE: 110°01'46.91262" W
ELLIPSOID HEIGHT: 5593.70'
(GEOID 03 CONUS)

PUBLIC LAND SURVEY SYSTEM GCDB ID NO.
UT300010S0010W0_200340

CERTIFICATION

I Jerry D. Allred, Professional Land Surveyor, State of Utah, do
hereby certify that I have performed or reviewed the work done on the
diagrammed corner as reported on this recordation form and approve same

Date 28 FEB 2018

Jerry D. Allred, Professional Land Surveyor
Certificate No. 148951
Duchesne County Surveyor

